

Appendix

Cross Reference FLR

Replaced Type	Type	Description
ERV...	FLR-S	Process connection: mounting thread upwards
ARV...	FLR-S	Process connection: mounting thread downwards
AFV...	FLR-S	Process connection: flange connection
AFVEC...	FLR-S	Material: Stainless steel 1.4571 E-CTFE-coated ; Option: anti-static
AFVTF...	FLR-S	Material: Stainless steel 1.4571 PTFE-coated ; Option: anti-static
AF-ADF...	FLR-S	Approval: ATEX Ex-d; Process connection: flange connection
NMG125...	FLR-S	Approval: ATEX Ex-i
AMRV...	FLR-H	Food industry design, Process Connection: Dairy fitting
AFCV...	FLR-H	Food industry design, Process Connection: Clamp connection
ERP...	FLR-P	Material: PVC; Process connection: mounting thread upwards
APRP...	FLR-P	Material: PVC; Process connection: mounting thread downwards
APFP ...	FLR-P	Material: PVC; Process connection: flange connection
ERPP...	FLR-P	Material: Polypropylen; Process connection: mounting thread upwards
ABRPP ...	FLR-P	Material: Polypropylen; Process connection: mounting thread downwards
APFPP ...	FLR-P	Material: Polypropylen; Process connection: flange connection
ERPF...	FLR-P	Material: Polypropylen; Process connection: mounting thread upwards
APRPF ...	FLR-P	Material: PVDF; Process connection: mounting thread downwards
APFPF ...	FLR-P	Material: PVDF; Process connection: flange connection

Type Code

Code	1st key	2nd key	3rd key
1	Electrical connection	Process connection	Material process connection
.../.../...	- (none) - connection cable	ER Mounting thread upwards (BSP)	V Stainless steel 1.4571
	A Terminal box Aluminium	R Mounting thread downwards (BSP)	VE Stainless steel electro-polished
	AB Terminal box Polypropylene	ENPT Mounting thread upwards (NPT)	VEC Stainless steel ECTFE-coated
	AP Terminal box Polyester	NPT Mounting thread downwards (NPT)	VTF Stainless steel PTFE-lined
	AV4 Terminal box Stainless steel 1.4571 with screw cap	MR Dairy fitting acc. to DIN 11851	T Titanium
	ADF Terminal box Aluminium flameproof	F Flange (DIN, ANSI, JIS)	HC Hastelloy C
	ASC4 Coupler plug C 164-232-F-4P	FC Clamp-connection acc. to DIN 32676	P PVC
	ASN6R Hirschmann coupler plug N6RAM 2D M20	IS Sanitary nozzle (Ingoldstutzen)	PP Polypropylene
	ASM12 Plug M12x1-4-pole		PF PVDF
2	Process connection		
.../.../...	... Mounting thread size in inches		
	... Dairy pipe fitting size DN 50 - DN 150		
	.../ Flange nominal size	.../ Flange pressure rating	... Flange face
DIN	DN 50 - DN 200	PN 6 - PN 100	Standard Form C optional E, A, F, N
DIN	DN 50 - DN 200	PN 6 - PN 100	Standard Form B1 optional B2, A, C, D
EN			Standard RF optional RTJ, FF, LT, LG
ANSI	2" - 8"	Class 150 - 600	Standard RF optional RTJ, FF, LT, LG
JIS	3/8" (DN 10) - 4" (DN 100)	5 K- 63 K	
Clamp	DN 25 - DN 100; 1" - 4"		

3	Guide tube material			Contact function		Optional code adder	
.../.../...	V	Stainless steel 1.4571	K 18	18 mm	/HT..	High temperature* +150 °C ... +200 °C	
	VE	Stainless steel electro-polished	K 15	15 mm	/TT..	Low temperature -10 °C ... -80 °C	
	VEC	Stainless steel ECTFE-coated	K 10	10 mm		* only contact separations 5/10/15 mm	
	VTF	Stainless steel PTFE-lined	K 5	5 mm	/PT100	Temperature probe PT 100 (2-,3- or 4-core)	
	HC	Hastelloy C			/..TH..	Temperature switch ... °C - closing or opening	
	P	PVC					
	PP	Polypropylene					
	PF	PVDF					
4	Option, Head-mounted transmitter in terminal box						
	TS	2-wire standard analogue	T53F	Intrinsically safe Foundation Fieldbus programmable			
	TE	2-wire intrinsically safe analogue	T53P	Intrinsically safe Profibus PA programmable			
	T32.1S	2-wire intrinsically safe HART® programmable	TLH	2-wire HART® programmable with LCD display			
	T32.xS	2-wire HART® programmable	TLEH	2-wire intrinsically safe HART® programmable with LCD display			
	T12	universally programmable	none	-			
5	Guide tube length			OD Guide tube			
L.../...	L.../	length in mm	...	OD in mm			
6	Float design			Durchmesser			
.../...	.../	Material (code 3, 1st key)	...	Float OD in mm			
7	Connection cable			Cable material			
.../...	.../	length in meter	—	PVC, grey			
			blue	PVC, blue			
			SIL	Silicone			
			PUR	PUR			
8	Approval						
.../.../...	-	none	GL	Germanischer LLoyd			
	Ex	Ex i	DNV	Det Norske Veritas			
	Ex d	ATEX	ABS	Bureau Veritas			
	Ex d	IECEX	3-A	3-A certified			

Ordering Example

	Electrical Connection		Process Connection		Guided tube material		Option	Guide tube		Float	Cable		Approval
	design / material		size		contact separation		transmitter	length / Ø			length / material		
Code	1	-	2	-	3	-	4	5	-	6	7	-	8
	AFV	-	50/6/F	-	VK 15/TT30	-	TS	L950/12	-	V44R	-	-	-

© 2014 KSR KUEBLER Niveau-Messtechnik AG, all rights reserved.
The specifications given in this document represent the state of engineering at the time of publishing.
We reserve the right to make modifications to the specifications and materials.



D-Ex Instruments, s.r.o.
Optátova 708/37
637 00 Brno/Czech Republic
Mob. +420 775 757 225
Tel. +420 541 423 225
ksr@dex.cz
www.dex.cz/ksr



D-Ex Instruments, s.r.o.
Pražská 3222/1
811 04 Bratislava/Slovakia
Mob. +420 775 757 225
Tel. +421 2 5729 7421
info@dex.sk
www.dex.sk/ksr



KSR KUEBLER Niveau-Messtechnik AG
Heinrich-Kuebler-Platz 1
69439 Zwingenberg/Germany
Tel. +49 6263 87-0
Fax +49 6263 8799
info@ksr-kuebler.com
www.ksr-kuebler.com